
SAFETY DIRECT LTD.



Fall Protection Equipment Manufacturer

P.O. Box 3026
Sherwood Park, Alberta T8H 2T1

Phone: (780) 464-7139 Fax: (780) 464-7652
e-mail: [inquiries@ safetydirect.ca](mailto:inquiries@safetydirect.ca)
Web site: www.safetydirect.ca

Instructions for the installation of MSRA 2 Permanent Roof Anchor.

WARNING

Failure of the user to read and understand all instructions for the use of this product may result in serious injury or death.

It is recommended that the user complete an approved fall protection program before using this equipment.

General instructions

All users must understand the relevant regulations and usage standards for fall protection applicable to this product, in the jurisdiction in which it is being used.

This equipment must only be installed and used by trained and competent personnel.

All fall protection equipment should be visually inspected before each use.

This equipment should not be altered or modified in any way.

All equipment that has been subjected to a fall incident must be removed from service immediately.

Installation Procedure

The anchor must be installed directly on a truss with the preformed bend on the anchor coincident with the peak of the truss. The anchor should be fastened to the truss by using 4" Ardox nails or a minimum 3 ½"#8 screws, and must have a nail or screw in each predrilled hole.

Failure to install the specified fasteners in all the predrilled holes will result in the anchor not generating its full rated capacity. It is rated for 2 people on opposite sides of the roof peak, but rated for only 1 person when workers are on the same side of the roof peak.

The shingling crew can use the temporary anchor until they reach the permanent anchor point. The anchor should then be removed and re-installed after the shingles have been placed. Care should be exercised to ensure that the nails or screws extend into the solid lumber of the truss and not just the roof sheathing.

When installing the cap shingles the anchor is sheathed over and the D-rings remain accessible, protruding below the cap shingle on both sides of the roof.

Fall Protection You Can Live With®

All rights reserved. No part of these instructions, covered by the copyrights herein, may be reproduced or copied in any form or by any means, including photocopying, recording, taping, or information storage and retrieval systems, without the written consent of Safety Direct Ltd. Copyright © 2005 Ref: 02/17