
SAFETY DIRECT LTD.



Fall Protection Equipment Manufacturer

P.O. Box 3026
Sherwood Park, Alberta T8H 2T1

Phone: (780) 464-7139 Fax: (780) 464-7652
e-mail: inquiries@safetydirect.ca
Web site: www.safetydirect.ca

Instructions for the installation of MRRA 1 Temporary Roof Anchor

WARNING

This anchor is rated for use by one (1) person only.

Failure of the user to read and understand all instructions for the use of this product may result in serious injury or death.

It is recommended that the user complete an approved fall protection program before using this equipment.

General instructions

All warning labels and instructions must be understood and followed by the user before using the product.

All users must understand the relevant regulations and usage standards for fall protection applicable to this product, in the jurisdiction in which it is being used.

This equipment must only be installed and used by trained and competent personnel.

All fall protection equipment should be visually inspected before each use.

This equipment should not be altered or modified in any way.

All equipment that has been subjected to a fall incident must be removed from service immediately.

Installation Procedure

The anchor must be installed directly on a truss with the preformed angle in the anchor coincident with the peak of the truss. The anchor should be fastened to the truss by using 4" Ardox nails, and must have a nail in each predrilled hole. Care should be taken to ensure that the nails are driven into the solid lumber of the truss and not into the roof sheathing alone.

Failure to install the specified fasteners in all the predrilled holes will result in the anchor not generating its full rated capacity.

The sheathing/shingling crews can use the temporary anchor until they reach the stage of shingling over the anchor. The anchor should then be removed or the upper portion of the anchor can be bent over so that the shingling can be completed.

Fall Protection You Can Live With®

Copyright (C) 2005 Safety Direct Ltd.