

## NYLON NON-ENERGY ABSORBING ADJUSTABLE SINGLE LEG LANYARD

MLNW3	{	03 3 ft	{	000 Snap Hook
		04 4 ft		001 Ladder Hook
		05 5 ft		002 Scaffold Hook
		06 6 ft		

Adjustable lanyards are the most versatile because they can be easily changed to a different length. This single leg non-energy absorbing lanyard is used to connect the worker to a secure anchor point. The snap hook nearest to the label attaches to the D-ring on the back of the harness, and the other end connects to the anchor point.

MLNW306002



### Features:

- ◆ Can be changed from its full length down to 18 in (457 mm)
- ◆ Optional connectors
  - ladder or scaffold hook in steel
  - snap or scaffold hook in aluminum
  - carabiner

### Specifications:

- ◆ 1 ¾ inch (45 mm) woven nylon webbing (Minimum tensile strength 5000 lbs 22.5 kN)
- ◆ Non-energy absorbing
- ◆ Maximum free fall distance CANNOT exceed 2 ft (610 mm)
- ◆ Capacity 1 person 310 lbs (140 kg)



**CERTIFIED** All lanyards meet or exceed CSA Z259.11-05 and comply with ANSI Z359.1-2007

Manufacturer



Safety Direct Ltd.  
Sherwood Park AB Canada  
[www.safetydirect.ca](http://www.safetydirect.ca)

Authorized Distributor