

# NYLON ENERGY ABSORBING (E4) SINGLE LEG LANYARD

<b>MLSN1</b>	{	<b>03</b> 3 ft	{	<b>000</b> Snap Hook
		<b>04</b> 4 ft		<b>001</b> Ladder Hook
		<b>05</b> 5 ft		<b>002</b> Scaffold Hook
		<b>06</b> 6 ft		<b>003</b> Tieback Hook

This single leg Class E4 energy absorbing lanyard is used to connect the worker to a secure anchor point. The snap hook nearest to the energy absorber attaches to the D-ring on the back of the harness, and the other end connects to the anchor point.

## Features:

- ◆ Class E4 energy absorber
- ◆ Clear heat shrink tubing protects the product labels and enables inspection of the energy absorber
- ◆ Available connectors
  - snap or ladder or scaffold hook in steel
  - snap or scaffold hook in aluminum
  - carabiner in steel or aluminum
  - tieback hook
- ◆ Also available as an adjustable lanyard

## Specifications:

- ◆ 1 inch (25 mm) durable nylon webbing  
Minimum tensile strength 5000 lb (22.5 kN)
- ◆ Maximum deployment length is 42 in (1067 mm)
- ◆ Maximum free fall distance CANNOT exceed 6 ft (1830 mm)
- ◆ Total weight of worker including equipment and clothing must be at least 100 lb (45 kg) and no more than 254 lb (115 kg)
- ◆ Higher weight workers should use an E6 energy absorber



**CERTIFIED** All lanyards meet or exceed CSA Z259.11-05 and comply with ANSI Z359.1-2007

Manufacturer



Safety Direct Ltd.  
Sherwood Park AB Canada  
[www.safetydirect.ca](http://www.safetydirect.ca)

Authorized Distributor