

POLYESTER ENERGY ABSORBING (E4) SINGLE LEG LANYARD

MLSW1	{	02 2 ft	{	000 Snap Hook
		03 3 ft		001 Ladder Hook
		04 4 ft		002 Scaffold Hook
		05 5 ft		
		06 6 ft		

This single leg Class E4 energy absorbing lanyard is used to connect the worker to a secure anchor point. The snap hook nearest to the energy absorber attaches to the D-ring on the back of the harness, and the other end connects to the anchor point.

Features:

- ◆ Class E4 energy absorber
- ◆ Clear heat shrink tubing protects the product labels and enables inspection of the energy absorber
- ◆ Optional maximum visibility polyester and Kevlar® webbing
- ◆ Available connectors
 - snap or ladder or scaffold hook in steel
 - snap or scaffold hook in aluminum
 - carabiner in steel or aluminum
- ◆ Also available as an adjustable lanyard

Specifications:

- ◆ 1 ¾ inch (45 mm) woven polyester webbing (Minimum tensile strength 5000 lbs 22.5 kN)
- ◆ Maximum deployment length is 42 in (1067 mm)
- ◆ Maximum free fall distance CANNOT exceed 6 ft (1830 mm)
- ◆ Total weight of worker including equipment and clothing must be at least 100 lb (45 kg) and no more than 254 lb (115 kg)
- ◆ Higher weight workers should use an E6 energy absorber



CERTIFIED All lanyards meet or exceed CSA Z259.11-05 and comply with ANSI Z359.1-2007

Manufacturer



Safety Direct Ltd.
Sherwood Park AB Canada
www.safetydirect.ca

Authorized Distributor