

## 7 ft (2.1 m) CSA Type 1 ANSI Class A Web Retractable

<b>RDW07A</b>	<b>000</b>	Forged Steel Snap Hook
	<b>000A</b>	Aluminum Snap Hook
	<b>001</b>	Forged Steel Ladder Hook
	<b>002</b>	Forged Steel Scaffold Hook
	<b>002A</b>	Aluminum Scaffold Hook
	<b>900</b>	Soft Loop

Safety Direct's retractable lifelines are designed as a single-person fall protection device. The RDW07A features a swivel eye for maximum mobility, a durable housing, and a unique braking system to reduce the forces in the event of a fall.

### Weight of Unit

2.8 lb (1.2 kg)

### Materials

Light weight aluminum housing  
1 in (25 mm) Dyneema webbing with sewn in fall indicator  
Double locking steel carabiner  
Optional hook configurations

### Webbing

Length 7 ft (2.1 m) Tensile Strength 4200 lb (19 kN)

### Hook Rating

5000 lb (23 kN) Tensile Strength 3600 lb (16 kN) Gate Rated

### Arresting Force

Maximum 1800 lb (8 kN) Average 1350 lb (6 kN)

### Maximum Arresting Distance

24 in (600 mm)

### Maximum Working Load

310 lb (140 kg)



**CERTIFIED** Meets CSA:Z259.2.2-98 ANSI:Z359.14-2014 ANSI:A10.32-2004 OSHA:1926.502

Manufacturer



Safety Direct Ltd.  
Sherwood Park AB Canada  
[www.safetydirect.ca](http://www.safetydirect.ca)

Authorized Distributor