

# Dual Leg 7 ft (2.1 m) CSA Type 1 ANSI Class A Web Retractable

**RDW07A** { 000AY Aluminum Snap Hooks  
002AY Aluminum Scaffold Hooks

Safety Direct's retractable lifelines are designed as a single-person fall protection device. This model uses two 7 foot retractables in a dual leg configuration for 100% tie-off. The unit attaches directly to the harness in the same space as the dorsal D-ring. It uses an auto-locking carabiner for the single attachment point and includes a special retaining clip to balance the two units. The dual retractable uses only aluminum hooks to keep the overall weight to a minimum.

## Each unit features

- Light weight aluminum housings
- 1 in (25 mm) Dyneema webbing
- Sewn in fall indicators
- Triple locking steel carabiner
- Durable polymer retaining clip
- Aluminum hooks

## Weight

6.0 lb (2.8 kg)

## Webbing

Length 7 ft (2.1 m) Tensile Strength 4200 lb (19 kN)

## Hook Rating

5000 lb (23 kN) Tensile Strength 3600 lb (16 kN) Gate Rated

## Arresting Force

Maximum 1800 lb (8 kN) Average 1350 lb (6 kN)

## Maximum Arresting Distance

24 in (600 mm)

## Maximum Working Load

310 lb (140 kg)



**CERTIFIED** Meets CSA:Z259.2.2-98 ANSI:Z359.14-2014 ANSI:A10.32-2004 OSHA:1926.502

Manufacturer

Authorized Distributor



Safety Direct Ltd.  
Sherwood Park AB Canada  
[www.safetydirect.ca](http://www.safetydirect.ca)