

10 ft (3.0 m) CSA Type 1 ANSI Class A Web Retractable

RDW10A	000	Forged Steel Snap Hook
	000A	Aluminum Snap Hook
	001	Forged Steel Ladder Hook
	002	Forged Steel Scaffold Hook
	002A	Aluminum Scaffold Hook
	900	Soft Loop

Safety Direct's retractable lifelines are designed as a single-person fall protection device. The RDW10A features a swivel eye for maximum mobility, a durable housing, and a unique braking system to reduce the forces in the event of a fall.

Weight of Unit
3.6 lb (1.6 kg)

Materials
Light weight aluminum housing
1 in (25 mm) Dyneema webbing with sewn in fall indicator
Double locking steel carabiner

Webbing
Length 10 ft (3.0 m) Tensile Strength 4200 lb (19 kN)

Hook Rating
5000 lb (23 kN) Tensile Strength 3600 lb (16 kN) Gate Rated

Arresting Force
Maximum 1800 lb (8 kN) Average 1350 lb (6 kN)

Maximum Arresting Distance
24 in (600 mm)

Maximum Working Load
310 lb (140 kg)



CERTIFIED Meets CSA:Z259.2.2-98 ANSI:Z359.14-2014 ANSI:A10.32-2004 OSHA:1926.502

Manufacturer

Authorized Distributor



Safety Direct Ltd.
Sherwood Park AB Canada
www.safetydirect.ca