

**Energy Absorbing Dual Leg  
Lanyards (E4)****PART #**  
**WSRYL250<sup>X</sup>E**  
(Replace "X" With Required Length)

This dual leg Class E4 Energy Absorbing lanyard complete with snap and ladder hooks, provides 100% tie off and is used for fall protection when working at heights.

**Features:**

- ◆ 1 ¾" Durable Polyester Webbing - Minimum Tensile Strength 5000lbs
- ◆ ¼" - 5/16" Vinyl Coated Aircraft Cable
- ◆ Class E4 Energy Absorber
- ◆ Clear Protective Heat Shrink Tube Over Energy Absorber to Protect Labels
- ◆ Snap and Ladder Hooks - 3600lb Gate Rating
- ◆ 100% Tie Off
- ◆ Total Mass of Worker Must be at least 45KG (100 lbs.) but not more than 115KG (254 lbs.)
- ◆ Energy Absorber Maximum Deployment Length is 42"

**Lengths:**

- ◆ Available from 3' to 6'
- ◆ Maximum free fall distance with an Energy Absorbing lanyard CANNOT exceed 6'.

**Applications:**

- ◆ Fall Arrest

**Applicable Standards:**

- ◆ All Lanyards meet and exceed CSA Z259. 11-05 and complies with ANSI Z359. 1-2007

**SAFETY DIRECT**

#100, 2210 Premier Way Sherwood Park, AB

Ph: (780) 464 - 7139 Fax: (780) 464 - 7652

[www.safetydirect.ca](http://www.safetydirect.ca)

Fall Protection You Can Live With